



27 g


[Anti-slip temples]



>> **Uses** (*)

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, carpentry, polishing, industry, laboratories, etc ... UV protection.

>> **Technical features**

- ✓ **Style:** Lightweight safety spectacles.
- ✓ **Treatment:** UV protection. Anti-scratch treatment
- ✓ **Lens thickness:** 2.00 mm.
- ✓ **Frame:** clear polycarbonate.
- ✓ **Lens:** bi-materials: polycarbonate and TPR.
- ✓ **Weight:** 27 grams.
- ✓ **Packing:** - carton of 100 units.
- box of 10 units (minimum of order).
- each unit under individual polybag. 

Learn more: www.singer.fr

>> **Advantages**

- ✓ Lightweight and modern safety eyewear.
- ✓ Outstanding field of vision and exceptional protection.
- ✓ Molded-in nose bridge provides uncompromised comfort and fit.
- ✓ Single-piece lens that will fit most faces.
- ✓ **ISO 9001** manufacturing ensuring a reliable and durable quality.
- ✓ Anti-slip temples for a better fit of the equipment on the face.



>> **Conformity**

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **BSI**. Notified body n°0086.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbol FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbol 1	Class 1: continuous works (better quality).
Scale number	Symbol 2C.1.2	Colour perception: not impaired Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor. This applies to UVC and most UVB radiation ^(b) . Typical source ^(a) : Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps. <i>(a) The example given for typical source is for general guidance.</i> <i>(b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm & 100 nm to 280 nm for UVC).</i>

Your distributor **SINGER® SAFETY**

