




Area of use*



Technical features

Cartridge filter against particles (aerosols).

Class: P3.

Adaptable to dedicated respiratory protection devices with a bayonet system ensuring a secure connection.

Compatible on **DMS2** and **DMT2** half-masks and on the **MP602** full-face mask from the **Singer® Safety** range.

To be used and sold by pair.

Weight (pair): ≈ 75 g.

Packaging: carton of 64 pairs.

Subpackaging: individual polybag (1 pair).



Advantages

Ultra-compact and lightweight design to ensure good air circulation, balanced weight and small footprint.

Comfortable wear thanks to better weight distribution and the simultaneous use of two cartridges attached to the side on compatible breathing apparatus.

Has a reinforced bayonet anchoring system, easy to fix.

Can be used on all DMS2, DMT2 or MP602 breathing apparatus.

Always use two cartridges of the same type.

Change both cartridges at the same time.



Certification

This product complies with **European Regulation (EU) 2016/425** on **Personal Protective Equipment (PPE)**.

Category III.

Issued by **CCQS Certification Services Limited**. Notified body n°2834.



CE 2834

EN 143 : 2021

Download the EU declaration of conformity on <https://docs.singer.fr>

STANDARDS	
EN 136	Respiratory protective devices: full face masks.
EN 140	Respiratory protective devices: half-masks and quarter-masks.
EN 143	Respiratory protective devices: filters against particles.
EN 14387	Respiratory protective devices: gas filters and combined filters.

CLASS OF FILTER (PARTICULATES) (EN 143)			
Class	Minimum filtration efficiency	Maximum penetration	Colour of filter
P1	80 %	20 %	White
P2	94 %	6 %	White
P3	99.95 %	0.05 %	White

EN 14387 - FILTER TYPE	
A (Brown)	Against gas and organic vapours with a boiling point ≥ 65°C specified by the manufacturer
AX (Brown)	Against certain organic gases and vapors with a boiling point ≤ 65°C specified by the manufacturer. (use limited to a single workday)
B (Grey)	Against certain gas and inorganic vapours specified by the manufacturer
E (Yellow)	Against sulphur dioxide, other gas, acid and vapours specified by the manufacturer
K (Green)	Against ammonia and organic derivatives of ammonia specified by the manufacturer
HgP3 (Red & white)	Against mercury vapors and particles (maximum usage time of 50 hours)
CLASS OF FILTER (GAZ)	
P1	Small capacity
P2	Medium capacity
P3	Large capacity
Classes are listed according to the type of environment No capacity class is assigned to AX or HgP3 filters.	

