


600g⁽¹⁾⁽¹⁾ Approximative weight of a shoe (smaller size)

Type of use (*)



Agriculture



Structural work



Logistics



Finishing work



Transport

Technical features

- ✓ High cut safety shoe.
- ✓ Upper in leather.
- ✓ Top of upper with polyester lining.
- ✓ Full piece removable footbed.
- ✓ Steel pierce resistant midsole and safety toe cap.
- ✓ Shock absorbing heel.
- ✓ Fastening with D ring and laces.
- ✓ **Colour:** black.
- ✓ **Sizes:** 37 to 47.
- ✓ **Packaging:**
 - Carton of 10 pairs.
 - Each pair individually packed in a box.

Learn more: www.singer.fr

Advantages

- ✓ Softness and comfort of leather.
- ✓ Comfortable lining.
- ✓ Very convenient removable insole.
- ✓ Dual-density PU outsole.
- ✓ Energy absorption of heel.
- ✓ Tongue with gusset.
- ✓ Simple but efficient and cost-effective style.



>> Conformity

This product has been tested according to the following European Standard:

- **EN ISO 20345: 2011** Personal protective equipment — Safety footwear

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE).

(Category II)

EU type examination certificate (**module B**) issued by **INTERTEK Italia Spa**. Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol S1-P	General requirement of the standard EN ISO 20345. Steel toe-protector absorbs an energy of 200 J + closed back, anti-static properties, heel energy absorption. Shoes with pierce resistant midsole up to 1100 newtons.
Slip resistance	Symbol SRC	(= SRA +SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol.