



## Area of use\*



## Technical features

### Bump cap.

**Material:** 55% polyester and 45% cotton.

ABS inner shell. Front peak: 7 cm.

Self grip fastening at the back

(Head circumference: 54-59 cm).

Side ventilation. Comfort foam.

**Color:** orange.

**Packaging:** carton of 60 pieces.

**Subpackaging:** bag of 10 pieces.



**AVAILABLE IN  
DIFFERENT COLORS**



## Advantages

Ventilated on each side.

Easy adjustement in the back.

Light weight and very convenient.

Comfort foam.

Manufacture under ISO 9001 certification.




## Certification

This product complies with **European Regulation (EU) 2016/425**

on Personal Protective Equipment (PPE). **Category II.**

Issued by **Alienor Certification**, notified body n°2754.

**EN 812 : 2012**



Download the EU declaration of conformity on <http://docs.singer.fr>

## STANDARDS

<b>EN 397</b>	Industrial safety helmet.
<b>EN 50365</b>	Electrically insulating helmets for use on low voltage installations.
<b>EN 13087-1 to 10</b>	Protective helmets: test methods.
<b>EN 812</b>	Industrial bump caps.
<b>EN 14052</b>	High performance industrial safety helmets.
<b>EN 12492</b>	Mountaineers helmets


### EN 397 - INDUSTRIAL SAFETY HELMET

<b>Obligatory requirements</b>	<ul style="list-style-type: none"> <li>- Shock absorption</li> <li>- Penetration resistance</li> <li>- Flame-resistance</li> <li>- Chin-strap anchorage points</li> <li>- Release of the chinstrap (between 150 and 250 N)</li> </ul>
<b>Optional requirements</b>	Optional additional requirements are applicable only when specifically demanded by the manufacturer of the helmet.

### EN 12492 – MOUNTAINEERS HELMETS

<b>Obligatory requirements</b>	<ul style="list-style-type: none"> <li>- Shock absorption</li> <li>- Penetration resistance</li> <li>- Ventilation</li> <li>- Resistance of the chinstrap (500 N)</li> </ul>
<b>Optional requirements</b>	Optional additional requirements are applicable only when specifically demanded by the manufacturer of the helmet.

### EN 50365 - ELECTRICALLY INSULATING HELMETS

	<p>For staff working on or near energized parts facilities not exceeding 1000 V AC or 1500 V DC (Class 0). These equipments, combined with other protections, should avoid dangerous currents to cross through the head.</p>
--	--

### EN 812 - INDUSTRIAL BUMP CAPS

This standard specifies the physical and performance requirements, the testing methods and the marking requirements of the bump caps for industry.

The bump caps for industry are intended to protect the wearer when he hits his head against hard and stationary objects with sufficient force to cause lacerations or other superficial injuries. They are not intended to protect from the effects of projections or the falling of suspended or moving objects or loads.

One should not confuse the bump caps for industry with the protection helmets for industry specified in EN 397.

## STANDARDS

<b>EN 352-1</b>	Hearing protectors. Part 1: Ear-muffs.
<b>EN 352-2</b>	Hearing protectors. Part 2: Ear-plugs.
<b>EN 352-3</b>	Hearing protectors. Part 3: Ears-muffs mounted on helmet (EN 397).

### DAILY MAXIMUM EXPOSURE TIME

<b>80 dB</b>	8 hours
<b>83 dB</b>	4 hours
<b>86 dB</b>	2 hours
<b>89 dB</b>	1 hour
<b>92 dB</b>	30 minutes
<b>95 dB</b>	15 minutes
<b>98 dB</b>	7 minutes and 30 seconds

### EN 352-1 - EARS-MUFFS

This standard specifies the requirements in field of construction, conception, performance and printing of ears-muffs as well as information for end-user.

It stipulates particularly the acoustic fading of ears-muffs in conformity with the EN 24869-1.

This standard does not apply to ear-muffs to be mounted on safety helmets or integrated to helmets.

### EN 352-2 - EARS-PLUGS

This standard specifies the requirements in field of construction, conception, performance and printing of ears-plugs as well as information for end-user.

It stipulates particularly the acoustic fading of ears-plugs in conformity with EN 24869-1 standard.

### EN 352-3 - EARS-MUFFS MOUNTED ON HELMET

This standard specifies the requirements for the construction, conception, performance and printing of ears-muffs mounted on safety industrial helmets in conformity with EN 397 standard as well as information for end-user. It stipulates particularly the acoustic fading of ears-muffs mounted on industrial helmets in conformity with EN 24869-1. As a same ear-muff can be mounted on different models or sizes of industrial safety helmets, the current part of standard specifies many physics and acoustic requirement depending the models or the helmetsize ear-muffs are mounted on. Requirements apply totally to the basic combination, that is to say helmet and ear-muffs mounted on one model or on one of the specified size of helmets. Requirements apply partially only to the additional combination, that is to say ear-muffs of the same model but attached on other helmets or sizes than the specified ones.