



Area of use*



CHEMICAL INDUSTRY



HEAVY INDUSTRIE



LIGHT INDUSTRY



BUILDING



AGRICULTURE

Technical features

Reusable twin filter full face panoramic respiratory protection mask.

Class 2.

Very soft and comfortable silicone facepiece.

Wide panoramic polycarbonate visor with anti-fog and anti-scratch treatment.

4-point harness made up of very easily adjustable straps and buckles.

Inner mask with two membranes facilitating air circulation and preventing the visor from misting up. Designed to accommodate two bayonet filters (sold separately).

Weight: ≈ 425 g.

Sizes: M & L.

Packaging: carton of 10 pieces.

Subpackaging: individual polybag.



Advantages

It includes a MAXi FLOW exhalation valve that efficiently reduces the temperature, humidity, and CO² content inside the respirator.

Valve protected with vertical descending flow cover.

Valve protected with vertical descending flow cover.

Four point harness for a safe, easy fit, a quick release and comfortable wear.

Polycarbonate visor with effective anti-fog & anti-scratch treatment.

Wide vision visor and light weight device for less fatigue during work. Better weight distribution thanks to two side filters.



Certification

This product complies with **European Regulation (EU) 2016/425** on **Personal Protective Equipment (PPE)**.

Category III.

Issued by **CCQS Certification Services Limited**. Notified body n°2834.



CE 2834

EN 136 : 1998

Download the EU declaration of conformity on <https://docs.singer.fr>

STANDARDS	
EN 136	Respiratory protective devices: full face masks.
EN 140	Respiratory protective devices: half-masks and quarter-masks.
EN 143	Respiratory protective devices: filters against particles.
EN 14387	Respiratory protective devices: gas filters and combined filters.

CLASS OF FILTER (PARTICULATES) (EN 143)			
Class	Minimum filtration efficiency	Maximum penetration	Colour of filter
P1	80 %	20 %	White
P2	94 %	6 %	White
P3	99.95 %	0.05 %	White

EN 14387 - FILTER TYPE	
A (Brown)	Against gas and organic vapours with a boiling point ≥ 65°C specified by the manufacturer
AX (Brown)	Against certain organic gases and vapors with a boiling point ≤ 65°C specified by the manufacturer. (use limited to a single workday)
B (Grey)	Against certain gas and inorganic vapours specified by the manufacturer
E (Yellow)	Against sulphur dioxide, other gas, acid and vapours specified by the manufacturer
K (Green)	Against ammonia and organic derivatives of ammonia specified by the manufacturer
HgP3 (Red & white)	Against mercury vapors and particles (maximum usage time of 50 hours)
CLASS OF FILTER (GAZ)	
P1	Small capacity
P2	Medium capacity
P3	Large capacity
Classes are listed according to the type of environment No capacity class is assigned to AX or HgP3 filters.	

