

S1P FO SR



>> Use (\*)

Especially suitable for works in logistics, tertiary sector. For all types of jobs requiring high mobility and comfort. Tiler, driver, warehousing, storage, printing, transport... (avoid use in highly aggressive or dirty environments).

>> Technical features

- ✓ Low cut safety shoes
- ✓ Split suede leather and ventilated polyester mesh.
- ✓ 200J shockproof steel toe cap.
- ✓ E.F.P. tongue.
- ✓ Ergonomic insole preformed in PU.
- ✓ Steel puncture resistant midsole.
- ✓ Double-density polyurethane sole.
- ✓ Black and grey colour, grey stitching.
- ✓ Sizes : 37 to 47.
- ✓ Packing : Carton of 10 pairs. Bundle of 1 pair.



Learn more : [www.singer.fr](http://www.singer.fr)



610g<sup>(1)</sup>

<sup>(1)</sup> (Approximative weight of a shoe, size 42)

>> Advantages

- ✓ Shoes sold with an extra pair of grey laces.
- ✓ Retro-reflective piping.
- ✓ Unique ergonomic Foam protect (E.F.P) system on collar: design & materials specifically designed to minimize compression, stabilize the lacing in order to provide optimum comfort and support.
- ✓ The composition and the structure of the Mesh lining allow the foot to breathe '«Clim pack»'.
- ✓ Dual density sole, antistatic, slip resistant, resistant to oils and hydrocarbons, produced by injection directly on the upper, ensures a high resistance to mechanical stress.

>> Conformity



This product has been tested according to the following European Standard:

- EN ISO 20345: 2022 Personal protective equipment — Safety footwear

It complies with the European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). CAT II.

EU type examination certificate (module B) issued CTC. Notified body n°0075.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Symbol S1P	General requirement of the standard EN ISO 20345: toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15 kN. + closed heel area + antistatic properties + energy absorption of seat region + perforation resistant midsole (metal insert type P)
Symbol FO	Resistance to fuel oil
Symbol SR	Slip resistance on ceramic tile with glycerol

Your distributor SINGER® SAFETY

