




Type of use (*)



Agriculture

Structural
work

Logistics

Finishing
work

Transport

Technical features

- ✓ Low cut safety shoe.
- ✓ Upper in leather.
- ✓ Top of upper with polyester lining.
- ✓ Full piece removable footbed.
- ✓ Steel pierce resistant midsole and safety toe cap.
- ✓ Shock absorbing heel.
- ✓ Fastening with D ring and laces.
- ✓ **Colour:** black.
- ✓ **Sizes:** 39 to 47.
- ✓ **Packaging:**
 - Carton of 10 pairs.
 - Each pair individually packed in a box.




590 g⁽¹⁾

⁽¹⁾ Approximative weight of a shoe (smaller size)

Learn more: www.singer.fr

Advantages

- ✓ Softness and comfort of leather.
- ✓ Comfortable lining.
- ✓ Very convenient removable insole.
- ✓ Dual-density PU outsole.
- ✓ Energy absorption of heel.
- ✓ Upper with water penetration and absorption treatment.
- ✓ Simple but efficient and cost-effective style.



Conformity

This product has been tested according to the following European Standard:

- **EN ISO 20345: 2011** Personal protective equipment — Safety footwear

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE).

(Category II)

EU type examination certificate (**module B**) issued by **INTERTEK Italia Spa**. Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol S3	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol SRC	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol