

## S3L HRO FO SR

730g<sup>(1)</sup><sup>(1)</sup> (Approximative weight of a shoe, size 42)Made  
under

## Area of use \*



LIGHT INDUSTRY



HEAVY INDUSTRY



PUBLIC WORKS

## Technical features

- ✓ High cut safety shoes
- ✓ Water repellent coated Nubuck leather metal hooks.
- ✓ 200J shockproof composite toe cap.
- ✓ E.F.P tongue.
- ✓ Ergonomic insole preformed in PU.
- ✓ Anti-puncture midsole in high tenacity textile.
- ✓ Sole : nitrile rubber, H.R.O.
- ✓ Black colour, grey stitching.
- ✓ Sizes : 38 to 47.
- ✓ Packing : Carton of 10 pairs.  
Bundle of 1 pair.

## Advantages

- ✓ ISO 9001 certified manufacturing.
- ✓ H.R.O Sole : contact heat resistant outsole compound.
- ✓ Energy absorbing heel.
- ✓ Good quality of workmanship and materials.
- ✓ Unique ergonomic Foam protect (**E.F.P**) system on collar: design & materials specifically designed to minimize compression, stabilize the lacing in order to provide optimum comfort and support.
- ✓ Anatomically-preformed PU insole: removable & quick drying. Support of the foot arch. Heel shock absorption.
- ✓ Polyester mesh lining for better perspiration absorption and quick drying.
- ✓ Highly resistant, non-magnetic and athermic fiberglass composite toecap.
- ✓ Anti-puncture midsole in high-tenacity textile for more flexibility, comfort and less fatigue at work every day.



## Conformity

This product has been tested according to the following European Standard:

- **EN ISO 20345: 2022** Personal protective equipment — Safety footwear

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **CAT II**.

EU type examination certificate (**module B**) issued **CTC**. Notified body **n°0075**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Symbol <b>S3L</b>	General requirement of the standard EN ISO 20345: toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15 kN. + closed heel area + antistatic properties + energy absorption of seat region + upper water penetration and absorption + cleated outsole + perforation resistant midsole (non-metal insert type PL)
Symbol <b>HRO</b>	Resistance to hot contact of the outsole
Symbol <b>FO</b>	Resistance to fuel oil of the outsole
Symbol <b>SR</b>	Slip resistance on ceramic tile with glycerol

Your distributor **SINGER® SAFETY**

**SINGER®**  
safety